



Product Service

Attestation of Conformity

No. N8A 072092 0289 Rev. 08

JAM60S14-xxx/PR, xxx= 305 to 325 in step of 5;
 JAM60S15-xxx/PR, xxx= 305 to 325 in step of 5;
 JAM60S16-xxx/PR, xxx= 305 to 325 in step of 5;
 JAM72S17-xxx/PR, xxx= 380 to 415 in step of 5;
 JAM60S17-xxx/PR, xxx= 315 to 345 in step of 5;
 JAM72S17-xxx/MR, xxx= 390 to 410 in step of 5;
 JAM60S17-xxx/MR, xxx= 320 to 340 in step of 5;
 JAM72S02-xxx/MR, xxx= 360 to 390 in step of 5;
 JAM60S02-xxx/MR, xxx= 300 to 340 in step of 5;
 xxx is standing for rated output power at STC

Parameters:

Construction:	Framed, with Junction box, Cable and Connectors.
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute; No. 10 West Kaifa Road, Yangzhou, 225009 Jiangsu, P. R. China
Application Class:	Class A
Maximum System Voltage:	1000 V DC or 1500 V DC

Tested according to:

EN 61730-1:2007/A11:2014
 EN 61730-2:2007/A1:2012

Page 4 of 4

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

TÜV SÜD
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證書 ◆ CERTIFICADO ◆ CERTIFICAT