

Attestation of Conformity

No. N8A 072092 0231 Rev. 03

Holder of Certificate: Shanghai JA Solar Technology Co., Ltd.

> No. 118. Lane 3111. West Huancheng Road Fengxian District 201401 Shanghai

PEOPLE'S REPUBLIC OF CHINA

Product: Crystalline Silicon Terrestrial Photovoltaic (PV) Modules

Mono-Crystalline Silicon Photovoltaic Module

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance.

It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.:

704061501205-10

Date,

2019-07-05

(Zhulin Zhang)

Page 1 of 2

SUD

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.





Attestation of Conformity

No. N8A 072092 0231 Rev. 03

Model(s):

JAM6(DG)-60-xxx/1500V, xxx= 250 to 270 in step of 5; JAM6(DG)-60-xxx/4BB/1500V, xxx= 260 to 285 in step of 5; JAM6(K)(DG)-60-xxx/PR/1500V, xxx= 270 to 305 in step of 5; JAM6(DG)-60-xxx/4BB/1500V, xxx= 260 to 280 in step of 5; JAM6(K)(DG)-72-xxx/PR/1500V, xxx= 330 to 365 in step of 5; JAM6(K)(DG)-72-xxx/4BB/1500V, xxx= 320 to 340 in step of 5; JAM60D00-xxx/PR, xxx= 270 to 315 in step of 5; JAM72D00-xxx/PR, xxx= 330 to 375 in step of 5; JAM60D00-xxx/SC, xxx= 260 to 285 in step of 5; JAM72D00-xxx/SC, xxx= 320 to 340 in step of 5; JAM60D00-xxx/BP, xxx= 285to 330 in step of 5; JAM72D00-xxx/BP, xxx= 340 to 390 in step of 5; JAM72D00-xxx/MB, xxx= 360 to 380 in step of 5; JAM60D00-xxx/MB, xxx= 295 to 315 in step of 5; JAM72D09-xxx/BP, xxx= 360 to 385 in step of 5; JAM60D09-xxx/BP, xxx= 300 to 320 in step of 5. JAM60D10-xxx/MB, xxx= 320 to 345 in step of 5; JAM72D10-xxx/MB, xxx= 385 to 410 in step of 5.

Parameters:

Construction:

Frameless, with Junction box.

Cable and Connectors. Yangzhou Opto-Electrical

Test Laboratory: Products Testing Institute

xxx is standing for rated output power at STC

No. 10 West Kaifa Road, Yangzhou,

225009 Jiangsu, P. R. China

Application Class:

Maximum System Voltage: 1500 V DC

Class A

Tested according to:

EN 61730-2:2007/A1:2012 EN 61730-1:2007/A11:2014