



## CERTIFICATE

No. Z2 072092 0285 Rev. 09

**Holder of Certificate:** 

Shanghai JA Solar Technology Co., Ltd.

No. 118, Lane 3111. West Huancheng Road Fengxian District 201401 Shanghai

PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



**Product:** 

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules

Poly-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.:

704061604126-17

Valid until:

2024-08-11

Date.

2019-08-14

(David Bo)



## CERTIFICATE

No. Z2 072092 0285 Rev. 09

Model(s):

1500 V DC Maximum System voltage, Fire Safety Class C Modules: JAP6(K)-72-xxx/4BB/1500V, xxx= 310 to 330 in step of 5: JAP6(K)-60-xxx/4BB/1500V, xxx= 255 to 275 in step of 5; 1500 V DC Maximum System voltage, Fire Safety Class A or Class C Modules: JAP72D00-xxx/SC,xxx= 310 to 340 in step of 5; JAP60D00-xxx/SC, xxx= 260 to 285 in step of 5; JAP72D00-xxx/PR, xxx= 330 to 345 in step of 5; JAP60D00-xxx/PR, xxx= 275 to 290 in step of 5; JAP72D09-xxx/SC, xxx= 330 to 345 in step of 5; JAP60D09-xxx/SC, xxx= 275 to 290 in step of 5; 1000 V DC Maximum System voltage, Fire Safety Class C Modules: JAP6(K)-72-xxx/4BB, xxx= 310 to 330 in step of 5; JAP6(K)-60-xxx/4BB, xxx= 255 to 275 in step of 5; JAP72S02-xxx/SC, xxx= 310 to 345 in step of 5; JAP60S02-xxx/SC, xxx= 255 to 290 in step of 5; JAP72S02-xxx/PR, xxx= 330 to 345 in step of 5; JAP60S02-xxx/PR, xxx= 275 to 285 in step of 5; JAP72S08-xxx/SC, xxx =320 to 345, in step of 5; JAP60S08-xxx/SC, xxx =270 to 290, in step of 5; JAP72S08-xxx/PR, xxx =335 to 355, in step of 5; JAP60S08-xxx/PR, xxx =280 to 295, in step of 5; 1000 V DC or 1500 V DC Maximum System voltage, Fire Safety Class C Modules: JAP72S01-xxx/SC, xxx= 310 to 345 in step of 5; JAP60S01- xxx/SC, xxx= 255 to 290 in step of 5; JAP72S01-xxx/PR, xxx= 330 to 345 in step of 5; JAP60S01-xxx/PR, xxx= 275 to 285 in step of 5: JAP72S03-xxx/SC, xxx =320 to 345, in step of 5; JAP60S03-xxx/SC, xxx =270 to 290, in step of 5; JAP72S03-xxx/PR, xxx =335 to 355, in step of 5; JAP60S03-xxx/PR, xxx =280 to 295, in step of 5; JAP72S09-xxx/SC, xxx= 320 to 340 in step of 5; JAP60S09-xxx/SC, xxx= 265 to 290 in step of 5; JAP72S10-xxx/SC, xxx= 335 to 350 in step of 5; JAP60S10-xxx/SC, xxx= 275 to 290 in step of 5; JAP72S01-xxx/MS, xxx= 325 to 340 in step of 5; JAP60S01-xxx/MS, xxx= 270 to 280 in step of 5; JAP72S03-xxx/MS, xxx= 320 to 345 in step of 5; JAP60S03-xxx/MS, xxx= 270 to 285 in step of 5 xxx is standing for rated output power at STC



œ ш



## CERTIFICATE

No. Z2 072092 0285 Rev. 09

Parameters:

Construction:

Framed or Frameless. with Junction box. Cable and Connectors.

Test Laboratory: Yangzhou Opto-Electrical Products Testing Institute

No. 10 West Kaifa Road, Yangzhou 225009 Jiangsu, P. R. China

Safety Class:

Maximum System Voltage:

Fire Safety Class:

Class II 1500 or 1000 V DC

Class C or Class A according to UL790.

**Tested** according to:

IEC 61215-1(ed.1) EN 61215-1:2016 IEC 61215-1-1(ed.1) EN 61215-1-1:2016 IEC 61215-2(ed.1) EN 61215-2:2017 IEC 61730-1(ed.2) EN 61730-1:2018 IEC 61730-2(ed.2) EN 61730-2:2018

**Production** Facility(ies): 072056, 072092, 079395, 090968, 095903, 097323, 101572, 001783, 089667, 102627, 102852, 104756, 104757, 078666, 090075, 076053, 078439

