



Product Service

CERTIFICATE

No. Z2 076729 0109 Rev. 01

Model(s):

SRP-xxx-6MA, (xxx=330-380, in step of 5)
 SRP-xxx-6MB, (xxx=275-315, in step of 5)
 SRP-xxx-6MA-HV, (xxx=330-380, in step of 5)
 SRP-xxx-6MB-HV, (xxx=275-315, in step of 5)
 SRP-xxx-E01A, (xxx=365-410, in step of 5)
 SRP-xxx-E01B, (xxx=305-340, in step of 5)
 SRP-xxx-E01A-HV, (xxx=365-410, in step of 5)
 SRP-xxx-E01B-HV, (xxx=305-340, in step of 5)
 SRP-xxx-BMA, (xxx=330-380, in step of 5)
 SRP-xxx-BMB, (xxx=275-315, in step of 5)
 SRP-xxx-BMC, (xxx=305-345, in step of 5)
 SRP-xxx-BMA-HV, (xxx=330-380, in step of 5)
 SRP-xxx-BMB-HV, (xxx=275-315, in step of 5)
 SRP-xxx-BMC-HV, (xxx=305-345, in step of 5)
 xxx stands for rated output power at STC.

Parameters:

Safety Class:	Class II
Max. System Voltage:	1000V DC or 1500 V DC
Construction:	Framed, with Junction box, cable and connector.
Fire Safety Class:	Class C according to UL790
Severity of Salt Mist Test:	Level 6

Tested according to:

IEC 61215-1(ed.1)
 IEC 61215-1-1(ed.1)
 IEC 61215-2(ed.1)
 IEC 61730-1(ed.2)
 IEC 61730-2(ed.2)
 IEC 61701(ed.2)

Production Facility(ies):

076729, 004571, 095290, 098633

