

TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD TUV SUD
ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT



Product Service

CERTIFICATE

No. Z2 076729 0101 Rev. 05

Holder of Certificate: **Seraphim Solar System Co.,Ltd.**
 No.1-2, Hengyao Rd, Henglin Zhen
 Wujin District
 213101 Changzhou
 PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product:

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules
Mono-crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 704061801207-06

Valid until: 2024-07-08

Date, 2019-07-09 (Zhulin Zhang)

A4 / 07.17



Product Service

CERTIFICATE

No. Z2 076729 0101 Rev. 05

Model(s):

1500 V DC Maximum System voltage,
 Fire Safety Class C Modules:
 SRP-xxx-6MA-HV (xxx=330-380, in step of 5);
 SRP-xxx-6MB-HV (xxx=275-315, in step of 5);
 SRP-xxx-E01A-HV (xxx=365-410, in step of 5);
 SRP-xxx-E01B-HV (xxx=305-340, in step of 5);
 SRP-xxx-BMA-HV (xxx=330-400, in step of 5);
 SRP-xxx-BMB-HV (xxx=275-330, in step of 5);
 SRP-xxx-BMC-HV (xxx=305-365, in step of 5);

1000 V DC Maximum System voltage,
 Fire Safety Class C Modules:
 SRP-xxx-6MA (xxx=330-380, in step of 5);
 SRP-xxx-6MB (xxx=275-315, in step of 5);
 SRP-xxx-E01A (xxx=365-410, in step of 5);
 SRP-xxx-E01B (xxx=305-340, in step of 5);
 SRP-xxx-BMA (xxx=330-400, in step of 5);
 SRP-xxx-BMB (xxx=275-330, in step of 5);
 SRP-xxx-BMC (xxx=305-365, in step of 5);

1500 V DC Maximum System voltage,
 Fire Safety Class A Modules:
 SRP-xxx-6MA-BG (xxx=350-375, in step of 5);
 SRP-xxx-6MB-BG (xxx=295-310, in step of 5);
 SRP-xxx-6MA-DG (xxx=350-375, in step of 5);
 SRP-xxx-6MB-DG (xxx=295-310, in step of 5);
 SRP-xxx-BMA-BG (xxx=350-385, in step of 5);
 SRP-xxx-BMB-BG (xxx=290-320, in step of 5);
 SRP-xxx-BMC-BG (xxx=320-350, in step of 5);
 SRP-xxx-BMA-DG (xxx=350-385, in step of 5);
 SRP-xxx-BMB-DG (xxx=290-320, in step of 5);
 SRP-xxx-BMC-DG (xxx=320-350, in step of 5).
 xxx is standing for rated output power at STC.

Parameters:

Safety Class:	Class II
Max. System Voltage:	1000V DC or 1500V DC
Test Laboratory:	Yangzhou Opto-Electrical Product Testing Institute No.10 West Kaifa Road, Yangzhou, 225009 Jiangsu P.R.China
Construction:	Framed or Frameless, with Junction box, cable and connector.
Fire Safety Class:	Class C or Class A according to UL790

Tested according to:

IEC 61215-1(ed.1)
 IEC 61215-1-1(ed.1)
 IEC 61215-2(ed.1)
 IEC 61730-1(ed.2)
 IEC 61730-2(ed.2)

Production Facility(ies):

076729, 095290, 098633, 104077, 104590

TÜV SÜD
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT