Poly JT245PCe Series Polycrystalline Solar Module

There are no limits to what we can do. Our possibilities are endless.

You can buy solar technology anywhere today. But you don't receive the esperience that is behind it. As a global company, Jetion has worked on new innovations and ideas since it was founded in 2004, contributing significantly to a clean and environmently-friendly energy.

From highly efficient solar cells to complete solar energy installations, we offer sustainable solutions for increased performance and, at the same time, a healthier environment.

Jetion modules are particularly employed where long-term profitability, reliability and environmental issues are of great importance.



1 MW, Wirbenz, Germany

Specific conditions of guarantee and further information may be found at: **www.jetion.biz**



We guarantee the highest income, for a long life.

Product Warranty

• 12 years for materials and workmanship.

Peak Power Warranty

- 5 years + 1 month from the date of purchase against a power drop exceeding 7 % of min. power rating measured under STC.
- 10 years + 1 month from the date of purchase against a power drop exceeding 10 % of min. power rating measured under STC.
- 25 years + 1 month from the date of purchase against a power drop exceeding 20 % of min. power rating measured under STC.

Plus-Sorting

• With this plus-sorting we ensure that our customers pay for the watts they receive and guarantee the highest efficiency.

Key Features

- 60 polycrystalline solar cells.
- Strong aluminum frames in order to improve the bearing capacity and withstand strong wind.
- Special mounting holes on the frames for long and short side mounting.
- High transparency low iron tempered glass with enhanced stiffness and impact resistance.
- Advanced EVA encapsulation system with multilayer backsheets.

Applications:

- Ground Installation
- Residential and Industrial Rooftops
- Carports



Electrical Features


All parameters are given in relation to 25 °C ambient temperature, 1000 W/m2 irradiance and AM 1.5

Тур		JT225PCe	JT230PCe	JT235PCe	JT240PCe	JT245PCe
Max-Power	Pm(W)	225	230	235	240	245
Modul Power Range	(VV)	230 > Pm ≥ 225	235 > Pm ≥ 230	240 > Pm ≥ 235	245 > Pm ≥ 240	Pm ≥ 245
Power Tolerance	(VV)	+0 ~ +5	+0 ~ +5	+0 ~ +5	+0 ~ +5	+0 ~ +5
Max-Power Voltage	Vm(W)	30	30.2	30.5	30.8	31.1
Max-Power Current	lm(A)	7.5	7.62	7.71	7.8	7.89
Short-Circuit Current	lsc(A)	8.2	8.31	8.4	8.55	8.65
Open-Circuit Voltage	Voc(V)	36.6	36.9	37	37.2	37.4
Max-System Voltage	(VDC)	600 V(UL)/1.000 V(IEC)				
Cell Efficiency	(%)	15.4	15.8	16.1	16.4	16.8
Module Efficiency	(%)	13.7	14	14.3	14.6	14.9
Max. Series Fuse	(A)	15				
Pm Temperature Coefficients	(%/°C)	-0.4336				
Isc Temperature Coefficients	(%/°C)	0.0825				
Voc Temperature Coefficients	(%/°C)	-0.4049				
NOCT Nominal Operating Cell 1	emperati	ire	45 ±2 °C			

Maximum load rating: 5.400 Pa (112,78 lbf/ft²)

Mechanical Characteristics

Cable type, Diameter and Length	4 mm ² , TUV certified, 1.000 mm		
Type of Connector	Compatible Type IV		
Number, type and arrangement of cells	60 pcs, polycrystalline silicone (6x10)		
Cell size (mm)	156x156		
Dimension (mm)	1655x992x40		
Weight (kg)	22.5		
No. of Draining Holes in Frame	10		
Bypass-Diods	6		
Glass, Type and Thickness	High Transmission, Low Iron Tempered Glass 3.2 mm		



Packaging Configuration

Packing Configuration: 24 pcs in box Quantity/Pallet: 48 pcs on pallet Loading Capacity: 624 pcs in container (40 ft)


Absolute Ratings

Dielectric Insulation Voltage: $3000 \vee$ Operating Temperature (°C): $-40 \sim +85$ Storage Temperature (°C): $-40 \sim +85$


Certificates

IEC 61215.2 / IEC 61730 / UL 1703.3rd

I-V Curves at different Irradiances (AM 1.5 25 °C)



PV CYCLE





EPIA



Specifications included in this datasheet are subject to change without prior notice.

JETION SOLAR EUROPE



Jetion Solar (Europe) Ltd. | Industriering 10 | 9491 Ruggell | Liechtenstein T: +423 265 3830 | F: +423 265 3839 | E: info@jetion.biz | www.jetion.biz