

Options and Accessories



Turn Signals



Soft Enclosure



Heavy-Duty Bumper/
West Coast Mirror



Wheel Covers



Fold-Down
Windshield



Battery Warning
Indicator



Canopy Top
White



Fuel Gauge
and Hour Meter



Custom Van Box



Stake-Side Kit



Certified ROPS
Cab Enclosure




Trailer Hitch



Pintle Hitch



Cab Heater



Safety Strobe Light



Toolbox

Value Packages

	Heavy-Duty Bumper	Trailer Hitch	Hour Meter*	Differential Guard	Radio/Beverage Holder	Cargo Box/Flat Bed**	Extra-Traction Rear Tires	8.5-Inch Premium Tread Front Tires
Carryall 1 Electric	✓	✓	✓	✓	✓	✓	✓	Standard
Carryall 1 Gasoline	✓	✓	Standard	✓	✓	✓	✓	Standard

* Fuel Gauge/Hour Meter is standard on all gas vehicles listed.
** Priced separately from base vehicle.

Club Car supports only the safe and legal use of our products. To reduce the risk of injury, always operate and travel within these vehicles in a safe, lawful and conscientious manner. The vehicles referenced herein are designed and manufactured for off-road use only. As such, they do not conform to Federal Motor Vehicle Safety Standards for automobiles or Low Speed on-road motor Vehicles. For further information on these products (including a full description of the Limited Warranty), please review the applicable owner's manual or contact Club Car, Inc.



Ingersoll Rand is a global diversified firm providing products, services and solutions to enhance the quality and comfort of air in homes and buildings, transport and protect food and perishables, secure homes and commercial properties, and increase industrial productivity and efficiency. Driven by a 100-year-old tradition of technological innovation, we enable our customers to create progress and a positive impact in their world.

1.800.CLUBCAR • +1 706.863.3000

www.clubcar.com www.ingersollrand.com

Club Car

CARRYALL 1 UTILITY VEHICLE



CARRYALL

1

From airports to colleges to zoos, the Carryall 1 is the perfect utility vehicle for light-duty jobs. The Carryall 1 is powered by your choice of a 351 cc, 11.5 hp gas engine or Club Car's IQ System™ electric motor. With the standard IQ System, the



Carryall 1 electric model features programmable speed control, consistent hill climbing and the overall performance that makes it feel more like a gas model. And Club Car's exclusive aluminum frame is up to three times stronger than comparable steel frames.

Features

Club Car's exclusive IQ System electric or 11.5 hp gas engine



9.1 ft³ (0.3 m³) cargo box carries 300 lb (136.1 kg)



Rugged, rustproof aluminum frame, chassis and cargo box



Self-adjusting rack & pinion steering




ArmorFlex® front body for fade-resistant color



Standard Color: Dark Gray



Optional Colors: Beige, Gray, Green, White, Classic Blue, Red, Black and Burgundy



4-ply, premium tread tires



Smooth, independent front and semi-independent rear suspension

Additional Features

- Maximum speed of 19 mph (30.6 kph) (Electric vehicles only)
- Side fuel fill
- 800 lb (363.2 kg) total vehicle capacity
- 48-volt IQ System electric motor or 351 cc, 11.5 hp gas, pedal-start engine
- Maximum hp @ 3,600 rpm exceeds SAE J1940 Performance Standards
- Reconfigured dash
- Redesigned hip restraint for maximum styling and comfort



Specifications

Carryall 1 Electric with exclusive IQ System



Carryall 1 Gasoline

	Carryall 1 Electric with exclusive IQ System	Carryall 1 Gasoline	
POWER SUPPLY	Engine	N/A	Kawasaki 4-cycle, OHV, 351 cc, single cylinder, air-cooled, pressure-lubricated, spin-on oil filter
	Drive Motor	48-volt Shunt/Sepex	N/A
	Horsepower	3.2 @ 2,400 rpm (continuous) 10.0 @ 1,125 rpm (intermittent)	11.5**
	Governor	N/A	Automatic ground speed sensing, internally geared-in unitized transaxle
	Governed RPM	N/A	3,050+/-30
	Ignition	N/A	Electronic w/electronic rpm limiter
	Drive Unit	12.3:1 direct-drive axle, double-reduction helical gear	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
	Electrical System	48-volt	12-volt, 500 CCA 105 min. reserve
	Batteries	Six 8-volt 117 min. @ 56 amp	N/A
	Charger	Automatic 48-volt DC, 17 amp, UL and CUL listed	N/A
Controller	300 amp Solid State	N/A	
STEERING/SUSPENSION	Steering	Self-adjusting rack & pinion	Self-adjusting rack & pinion
	Front Suspension	Independent leaf spring w/dual hydraulic shocks	Independent leaf spring w/dual hydraulic shocks
	Rear Suspension	Leaf springs w/dual hydraulic shocks	Leaf springs w/dual hydraulic shocks
	Brakes	Self-adjusting, rear-wheel, mechanical drum	Self-adjusting, rear-wheel, mechanical drum
	Park Brake	Foot-operated, multi-lock	Foot-operated, multi-lock
	Stabilizer Bar	No	Yes
FRAME/CHASSIS	Frame/Chassis	Aluminum I-Beam	Aluminum I-Beam
	Front Body	ArmorFlex®	ArmorFlex®
	Rear Body	All aluminum	All aluminum
	Body Finish	Matching paint over molded-in color	Matching paint over molded-in color
	Light Package	Optional	Optional
	Trailer Hitch	Optional	Optional
	Front Tires	18 x 8.50-8, 4-ply rated, Premium tread	18 x 8.50-8, 4-ply rated, Premium tread
	Rear Tires	18 x 8.50-8, 4-ply rated, Premium tread	18 x 8.50-8, 4-ply rated, Premium tread
	Instrumentation	Battery warning light	Electronic fuel gauge/hour meter, low-oil warning light
DIMENSIONS	Cargo Box Size	37.6" x 45.1" x 9.3" (9.1 ft ³) 95.6 cm x 114.6 cm x 23.5 cm	37.6" x 45.1" x 9.3" (9.1 ft ³) 95.6 cm x 114.6 cm x 23.5 cm
	Flat Bed Size	35.8" x 44.3" (90.8 cm x 112.4 cm)	35.8" x 44.3" (90.8 cm x 112.4 cm)
	Bed Height	27.5" (69.9 cm)	27.5" (69.9 cm)
	Bed Capacity	300 lb (136.1 kg)	300 lb (136.1 kg)
	Total Vehicle Capacity	800 lb (363.2 kg)	800 lb (363.2 kg)
	Overall Length	103.5" (262.9 cm)	103.5" (262.9 cm)
	Overall Width	48.0" (121.9 cm)	48.0" (121.9 cm)
	Overall Height	48.0" (121.9 cm)	48.0" (121.9 cm)
	Wheelbase	65.5" (166.4 cm)	65.5" (166.4 cm)
	Ground Clearance Under Differential	4.5" (11.4 cm)	4.5" (11.4 cm)
	Fuel Tank Capacity	N/A	7.0 gallons (26.5 Liters)
	Tread	34.5"/38.5" (87.6 cm/97.8 cm)	34.5"/38.5" (87.6 cm/97.8 cm)
	Dry Weight Less Batteries	530 lb (240.6 kg)	658 lb (298.7 kg)
	Speed Range	8-19 mph (12.8-30.6 kph)	12-15 mph (19.3-24.1 kph)
	Outside Clearance Circle	17.5 ft (5.3 m) dia.	17.5 ft (5.3 m) dia.
Turning Radius	8.4 ft (2.6 m)	8.4 ft (2.6 m)	
Intersecting Aisle Radius	72.0" (182.9 cm)	72.0" (182.9 cm)	
Vehicle Warranty	2-year limited/4-year batteries*	2-year limited	

*4-year, limited battery warranty for electric vehicles **Exceeds SAE J1940 Performance Standards