Options and Accessories



Lighting Package*



Canopy Top White

Cab Heater

(Gas Only)

Battery Warning Indicator



Electric Bed Lift



Pintle Hitch





Certified ROPS

Swisher Dump Cart



Heavy-Duty Bumper/ West Coast Mirror

Stake-Side Kit

Safety Strobe Light



Industrial Van Box



Heavy-Duty Batteries



Fold-Down Windshield



2-Inch Rear Receiver Hitch



Toolbox

Custom Van Box

| Value Packages | Heavy-Duty Bumper | Headlights | Trailer Hitch | Hour Meter† | Differential Guard | Radio/ Beverage Holder | Cargo Box/ Flat Bed ^{††} | Extra- Traction Rear Tires | 8.5-Inch Premium Tread Front Tires |
|---------------------|----------------------|--------------|------------------|----------------|-----------------------|------------------------------|--------------------------------------|----------------------------------|---|
| Carryall 2 Electric | Standard | \checkmark | Standard | ✓ | √ | √ | √ | Standard | Standard |
| Carryall 2 Gasoline | Standard | 1 | Standard | Standard | 1 | 1 | 1 | Standard | Standard |

40-Gallon Sprayer

* Includes horn, turn signals and brakelights. [†] Fuel Gauge/Hour Meter is standard on all gas vehicles listed. ^{††} Priced separately from base vehicle

Club Car supports only the safe and legal use of our products. To reduce the risk of injury, always operate and travel within these vehicles in a safe, lawful and conscientious manner. The vehicles referenced herein are designed and manufactured for off-road use only. As such, they do not conform to Federal Motor Vehicle Safety Standards for automobiles or Low Speed on-road motor Vehicles. For further information on these products (including a full description of the Limited Warranty), please review the applicable owner's manual or contact Club Car, Inc.



Ingersoll Rand is a global diversified firm providing products, services and solutions to enhance the quality and comfort of air in homes and buildings, transport and protect food and perishables, secure homes and commercial properties, and increase industrial productivity and efficiency. Driven by a 100-year-old tradition of technological innovation, we enable our customers to create progress and a positive impact in their world.

1.800.CLUBCAR • +1 706.863.3000

www.clubcar.com www.ingersollrand.com















Club Car, the world's largest producer of Zero Emission Vehicles, offers our exclusive IQ Plus System[™] on the Carryall 2 and 6 electric models. IQ Plus is the most advanced DC drive train technology in its class, improving energy management and increasing the usable range



of the vehicle, while enhancing the service capabilities of the 48-volt platform. Along with its best-in-class load-carrying capabilities, this leading edge electrical system allows the user to program speeds, motor braking and acceleration.





Additional Features

- Maximum speed of 17 mph (27.3 kph) (Electric vehicles only)
- 1,200 lb (544.8 kg) total vehicle capacity
- Maximum hp @ 3,600 rpm exceeds SAE J1940 Performance Standards
- Side fuel fill
- Ergonomic dash mount shifter
- 48-volt ZEV IQ Plus electric
- motor or 351 cc, 11.5 hp gas, pedal-start engine
- Redesigned hip restraint for maximum styling and comfort

| | Carryall 2 Electric | Carryall 2 Gasoline | | | |
|-------------------|---|--|--|--|--|
| Engine | N/A | Kawasaki 4-cycle, OHV, 351 cc, single cylinder, air-cooled, pressure-lubricated, spin-on oil filter | | | |
| Drive Motor | 48-volt shunt/sepex | N/A | | | |
| Horsepower | 3.7 @ 3,400 rpm (continuous) 21.0 @ 2,000 rpm (peak) | 11.5** | | | |
| Governor | N/A | Automatic ground speed sensing, internally geared-in unitized transaxle | | | |
| Governed RPM | N/A | 3,170+/-30 | | | |
| Drive Unit | 12.3:1 direct-drive axle, double-reduction helical gear | Electronic w/electronic rpm limiter, unitized transaxle, helical gears | | | |
| Electrical System | 48-volt | 12-volt, 500 CCA 105 min. reserve | | | |
| Batteries | Eight 6-volt, Standard: T105 = 115 min @ 75 amps; Heavy Duty: T145 = 145 min @ 75 amps | N/A | | | |
| Charger | Automatic, computer-controlled 48-volt DC, 17 amp, UL and CUL listed; International CE marked available | N/A | | | |
| Controller | 500 amp Solid State | N/A | | | |
| Steering | Self-adjusting rack & pinion | Self-adjusting rack & pinion | | | |
| Front Suspension | Independent leaf spring w/dual hydraulic shocks | Independent leaf spring w/dual hydraulic shocks | | | |
| Rear Suspension | Leaf springs w/dual hydraulic shocks | Leaf springs w/dual hydraulic shocks | | | |
| Brakes | Four-wheel, mechanical drum | Self-adjusting, two-wheel mechanical drum | | | |
| Park Brake | Foot-operated, multi-lock | Foot-operated, multi-lock | | | |
| Stabilizer Bar | No | Yes | | | |
| Frame/Chassis | Aluminum I-Beam | Aluminum I-Beam | | | |
| Front Body | ArmorFlex® | ArmorFlex® | | | |
| Rear Body | All aluminum | All aluminum | | | |
| | | Matching paint over molded-in color | | | |
| | Optional | Optional | | | |
| | | Standard | | | |
| | | 18 x 8.50-8, 6-ply rated, Premium tread | | | |
| Rear Tires | 18 x 8.50-8, 6-ply rated, Extra-Traction tread | 18 x 8.50-8, 6-ply rated, Extra-Traction tread | | | |
| Instrumentation | Battery warning light | Electronic fuel gauge/hour meter, low-oil warning light | | | |
| Cargo Box Size | 123.8 cm x 126.4 cm x 27.6 cm | 48.8" x 49.8" x 10.9" (15.3 ft ³) 123.8 cm x 126.4 cm x 27.6 cm | | | |
| | | 46.9" x 48.3" (119.1 cm x 122.7 cm) | | | |
| | | 27.5" (69.9 cm) | | | |
| . , | | 800 lb (363.2 kg) | | | |
| | , | 1,200 lb (544.8 kg) | | | |
| | | 111" (281.9 cm) | | | |
| | · · · · · | 50.0" (127.0 cm) | | | |
| | | 48.0" (121.9 cm) | | | |
| Ground Clearance | 4.5" (11.4 cm) | 77.5" (196.9 cm) 4.5" (11.4 cm) | | | |
| | N/A | 6.0 gallons (22.7 Liters) | | | |
| | | 6.0 gallons (22.7 Liters) 34.5"/38.5" (87.6 cm/97.8 cm) | | | |
| | | 724 lb (328.7 kg) | | | |
| | | 14-16 mph (22.5-25.7 kph) | | | |
| | | 20.7 ft (6.3 m) dia. | | | |
| | | 10.0 ft (3.0 m) | | | |
| | | 77.0" (195.6 cm) | | | |
| | | 2-year limited | | | |
| | HorsepowerGovernorGoverned RPMDrive UnitElectrical SystemBatteriesGotrollerControllerSteeringFront SuspensionRear SuspensionBrakesPark BrakeStabilizer BarFront BodyRear BodyBody FinishLight PackageTrailer HitchFront TiresRear TiresInstrumentationGargo Box SizeFlat Bed SizeBed HeightBed CapacityOverall LengthOverall HeightFund ClearanceUnder DifferentialFreadDry Weight Less BatteriesSpeed RangeOutside Clearance CircleTurning RadiusIntersecting Aisle RadiusVehicle Warranty | Horsepower3.7 @ 3,400 rpm (continuous) 21.0 @ 2,000 rpm (peak)GovernorN/AGoverned RPMN/ADrive Unit12.31 direct-drive axle, double-reduction helical gearElectrical System48-voltBatteriesEight 6-volt, Standard: T105 = 115 min @ 75 amps; Heavy Duty: 1145 = 145 min @ 75 ming; Heav Duty: 1145 = 145 min @ 75 ming; Heav Duty: 1145 = 145 min @ 75 ming; | | | |