


IT'S NOT A UTILITY VEHICLE.

IT'S A *Club Car*

 Ingersoll Rand



# CAN A UTILITY VEHICLE REALLY DO THAT?

## **Brains and brawn.**

**Now available in utility vehicles.**

For all the advancements Club Car® has introduced to turf utility vehicles, the motivation comes down to one simple result: Work ethic. Vehicles that go where you need them to go, doing the jobs you need them to do, day in, day out, without problems. That's what led us to develop exclusives like all-aluminum frames that won't rust and are significantly stronger than

competitors' steel frames; the IQ Plus System™, a performance breakthrough for electronic drive trains; IntelliTrak™, a revolutionary all-wheel drive system that senses the terrain and automatically engages all four wheels as the conditions demand more power. And that's just the beginning. As long as courses put high demands on our vehicles, we'll keep innovating new ways to get the jobs done.

# TURF 1



A versatile, multi-tasking machine that can out-manuever anything else in its class, the Carryall Turf 1 is up to any light-duty job you throw at it. Choose a gas engine or electric with Club Car's® exclusive IQ System™; either way, you have an energetic partner built for the long haul.

- Choice of 351 cc gasoline 11.5 hp engine or Club Car's exclusive IQ System 48-volt electric motor
- 800 lb (363.2 kg) Total Vehicle Capacity
- 9.1 ft<sup>3</sup> (0.3 m<sup>3</sup>) Cargo Box carries 300 lb (136.1 kg)
- Radio/Beverage Holder
- Differential Guard
- Heavy Duty Front Bumper
- Battery warning light standard
- Rustproof Aircraft Grade Aluminum Frame, Chassis & Cargo Box
- Self-adjusting, maintenance-free rack & pinion steering for easy handling
- Premium tread tires
- Heavy duty unitized powertrain



# TURF 2



When you want maneuverability with a little added muscle, the Carryall Turf 2 is your go-to guy. This economical yeoman is available in gas engine or electric with the IQ Plus System™, and can handle a variety of maintenance tasks, shouldering a full 1,200 pounds of vehicle capacity. Load it up, Turf 2 can take it.

- Choice of 351 cc gasoline 11.5 hp engine or Club Car's exclusive IQ Plus System 48-volt electric motor
- 1,200 lbs (544.8 kg) total vehicle capacity
- 15.3 ft<sup>3</sup> (0.4 m<sup>3</sup>) Cargo Box carries 800 lb (363.2 kg)
- Headlights
- Radio/Beverage Holder
- Differential Guard
- Heavy Duty Front Bumper
- Battery warning light standard
- Rustproof Aircraft Grade Aluminum Frame, Chassis & Cargo Box
- Self-adjusting, maintenance-free rack & pinion steering for easy handling
- Premium tread tires
- Heavy duty unitized powertrain



# TURF 6



It's all about return on investment these days and nothing fills that bill like the Carryall Turf 6. With 1,500 pounds of capacity and almost 6-feet of cargo bed, Turf 6 does it all. It's equipped with an 11.5 hp gas engine so you'll have all the power—and payload—you need for your operation's most demanding chores.

- 351 cc gasoline 11.5 hp engine
- 1,500 lbs (681 kg) total vehicle capacity with newly redesigned convenient under seat storage area
- 17.1 ft<sup>3</sup> Cargo Box with flip-down tailgate
- Headlights
- Radio/Beverage Holder
- Differential Guard
- Heavy Duty Front Bumper
- Battery warning light standard
- Rustproof Aircraft Grade Aluminum Frame, Chassis & Cargo Box
- Self-adjusting, maintenance-free rack & pinion steering for easy handling
- Premium tread tires
- Hour meter
- Heavy duty unitized powertrain



# TURF 252



If your to-do list is as long as your day, the rugged Carryall 252 with the IQ Plus System is the vehicle ready to go the distance. The high-output charger, controller, onboard computer and battery system give you fast charging and superior power and range. Prefer gas? There's an 11.5 hp, 351 cc gas engine that's primed to take on any challenge thrown its way.

- Choice of 351 cc gasoline 11.5 hp engine or Club Car's exclusive IQ Plus System 48-volt electric motor
- Headlights
- Radio/Beverage Holder
- Differential Guard
- Heavy Duty Front Brush Guard
- Battery warning light standard
- Rustproof Aircraft Grade Aluminum Frame, Chassis & Cargo Box
- Independent front suspension
- Rear suspension with heavy duty stabilizer bar



# CARRYALL 232

CARRYALL 232



## Run circles around the big boys.

Whoever said you can't be strong and nimble at the same time never met the Carryall 232. This mighty mite in the Club Car® line packs a whole lot of muscle in a smaller package. It can handle a total capacity of 800 pounds without breaking a sweat, while at the same time executing the tightest turning radius in its class. Which means there aren't many tight spots that the Carryall 232 can't get out of; and a lot of chores in hard-to-reach places on the course just got easier.

- Choice of gas or electric powertrain
- 800 lb/363.2 kg total vehicle capacity
- Generous 7.1 ft<sup>3</sup>/0.2 m<sup>3</sup>, 300 lb/136.1 kg bed box capacity
- Lightweight, rust-proof aluminum frame
- Durable, corrosion-resistant, composite bed box
- Scratch and impact resistant ABS Plastic front and ArmorFlex® rear body
- Self-adjusting rack & pinion steering
- Self-adjusting rear mechanical drum brakes with foot-operated park brake
- Smooth riding front and rear suspension
- Tightest turning diameter in class (17.4 ft/5.3 m)
- Greater operating range (7 gal/26.5L fuel tank)
- 2 year, 2000 hour limited warranty

# CARRYALL 295

CARRYALL 295



- All-aluminum rear body
- Automatic 4WD engagement with IntelliTrak
- Rack & pinion steering
- Swing arm rear suspension with coil-over shocks
- 4-wheel hydraulic disc brakes
- Electronic fuel gauge/hour meter, low oil warning light
- Automotive style parking brake
- Full pressure, spin-on oil filter

When your utility needs go to the next level, Club Car® has the solution.

Even when the job calls for duty at a higher level, Club Car® still has you covered. Our line of Carryall 295 vehicles are built to take on more with features like our exclusive IntelliTach™ 4-Wheel-Drive system, that automatically senses its environment and gives you power when you need it most. Or the 295 SE with four forward-facing seats and 6-point Roll Over Protective Structure (ROPS) for safety. And when you need some extra muscle, the Carryall 295 with IntelliTach™ quick-change attachment system lets you easily add attachments to handle jobs that would normally be out of the question. With a lineup this strong, the project possibilities are endless.

## 4x2 ACCESSORIES\*



Dial up the comfort, functionality and performance of your Utility Vehicles with genuine Club Car® Accessories. We offer a complete line of factory-installed and aftermarket accessories that let you customize your utility vehicles for the chores at hand. Want to keep working regardless of the weather, operate on tougher terrain, pull more, haul more or demand longer hours of service from your vehicles? Club Car has the accessories to get it done.

# Get More Done With Genuine Club Car® Accessories



Canopy Top



Heavy-Duty Front Bumper



Flatbed Tool Box



Cargo Box Tool Box



Driving Range Protective Enclosure




Universal Ball Picker Mount



ROPS Cab (Roll Over Protective Structure)



Cab Safety Strobe Light



Cab Outside Mirrors



Halogen Work Lights



Accessory Switch-Panel



Cab Fan Defogger



Hour Meter



Fuel Gauge/ Hour Meter



Heavy-Duty Batteries



Battery Capacity Indicator



On-Board Charger




Cab Heater



Van Box



1,700 lb. Winch



2,500 lb. Winch



Nerf Bars



Stake-side Kit



Swisher® Dump Cart



Electric Bed Lift



Trailer Hitch



2-Inch Front Receiver Hitch




2-Inch Rear Receiver Hitch



Wheel Cover




Premium Tread 4-Ply or 6-Ply Tires



Extra-Traction, 6-Ply Tires



Turf Tires



All-Terrain Tires



Mud Tires

\* For a complete listing of accessories, please contact your local Club Car dealer.

## 4x2 SPECIFICATIONS

	TURF 1		TURF 2	
	ELECTRIC	GASOLINE	ELECTRIC	GASOLINE
POWER SOURCE				
ENGINE	N/A	Kawasaki 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter	N/A	Kawasaki 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter
DRIVE MOTOR	48-volt shunt sepex	N/A	48-volt shunt/sepex	N/A
HORSEPOWER	3.2 hp @ 2,400 rpm (continuous), 10 hp @ 1,125 rpm (intermittent)	11.5 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards	3.1 hp @ 3,400 rpm (continuous), 21 hp @2,000 rpm (intermittent)	11.5 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards
GOVERNOR	N/A	Automatic ground speed sensing, internally geared-in unitized transaxle	N/A	Automatic ground speed sensing
GOVERNED RPM	N/A	3,050 +/- 30	N/A	3,170 +/- 30
IGNITION	N/A	Electronic with electronic limiter	N/A	Electronic with electronic limiter
DRIVE UNIT	12.3:1 direct-drive axle, double-reduction helical gear	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse	12.3:1 direct-drive axle, double-reduction helical gear	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
ELECTRICAL SYSTEM	48-volt	12-volt, 500 cca 105 min reserve	48-volt	12-volt, 500 CCA, 105 min. reserve
BATTERIES	Six 8-volt 117 min @ 56 amp	N/A	Eight 6-volt standard: T105 115 min @ 75 amps; heavy-duty T145 145 min @ 745 amps	N/A
CHARGER	Automatic 48-volt DC, 17 amp, UL and CUL listed	N/A	Automatic 48-volt DC, 17 amp, UL and CUL listed	N/A
CONTROLLER	250A solid state	N/A	500A solid state	N/A
KEY- OR PEDAL-START	Pedal	Pedal	Pedal	Pedal
STEERING	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion
FRONT SUSPENSION	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
BRAKES	Self-adjusting rear mechanical drum	Self-adjusting rear mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum
PARK BRAKE	Foot-operated, multi-lock	Foot-operated, multi-lock	Foot-operated, multi-lock	Foot-operated, multi-lock
FRAME/CHASSIS	Aluminum I-beam	Aluminum I-beam	Aluminum I-beam	Aluminum I-beam
FRONT BODY	ArmorFlex®	ArmorFlex®	ArmorFlex®	ArmorFlex®
REAR BODY	All aluminum	All aluminum	All aluminum	All aluminum
TIRES	18 x 8.50-8, 4-ply rated, premium tread	18 x 8.50-8, 4-ply rated, premium tread	18 x 8.50-8, 6-ply rated, premium tread	18 x 8.50-8, 6-ply rated, premium tread
INSTRUMENTATION	Battery warning light	Electronic fuel gauge/hour meter, low-oil warning light	Battery warning light	Electronic fuel gauge/hour meter, low oil warning light
CARGO BOX SIZE	37.6 in x 45.1 in x 9.3 in (9.1 ft³) 95.6 cm x 114.6 cm x 23.5 cm	37.6 in x 45.1 in x 9.3 in (9.1 ft³) 95.6 cm x 114.6 cm x 23.5 cm	48.8 in x 49.8 in x 10.9 in (15.3 ft³) 123.8 cm x 126.4 cm x 27.6 cm	48.8 in x 49.8 in x 10.9 in (15.3 ft³) 123.8 cm x 126.4 cm x 27.6 cm
FLAT BED SIZE	35.8 in x 44.3 in (90.8 cm x 112.4 cm)	35.8 in x 44.3 in (90.8 cm x 112.4 cm)	46.9 in x 48.3 in (119.1 cm x 122.7 cm)	46.9 in x 48.3 in (119.1 cm x 122.7 cm)
BED HEIGHT	27.5 in (69.9 cm)	27.5 in (69.9 cm)	27.5 in (69.9 cm)	27.5 in (69.9 cm)
BED CAPACITY	300 lb (136.1 kg)	300 lb (136.1 kg)	800 lb (362.9 kg)	800 lb (362.9 kg)
TOTAL VEHICLE CAPACITY	800 lb (363.2 kg)	800 lb (363.2 kg)	1,200 lb (544.8 kg)	1,200 lb (544.8 kg)
OVERALL LENGTH	103.5 in (262.9 cm)	103.5 in (262.9 cm)	111 in (281.9 cm)	111 in (281.9 cm)
OVERALL WIDTH	48 in (121.9 cm)	48 in (121.9 cm)	50 in (127 cm)	50 in (127 cm)
OVERALL HEIGHT	48 in (121.9 cm)	48 in (121.9 cm)	48 in (121.9 cm)	48 in (121.9 cm)
WHEELBASE	65.5 in (166.4 cm)	65.5 in (166.4 cm)	77.5 in (196.9 cm)	77.5 in (196.9 cm)
GROUND CLEARANCE	4.5 in (11.4 cm)	4.5 in (11.4 cm)	4.5 in (11.4 cm)	4.5 in (11.4 cm)
FUEL TANK CAPACITY	N/A	5.1 gal (19.2L)	N/A	5.1 gal (19.2L)
STABILIZER BAR	No	Yes	No	Yes
TREAD	34.5 in/38.5 in (87.6 cm/97.8 cm)	34.5 in/38.5 in (87.6 cm/97.8 cm)	34.5 in/38.5 in (87.6 cm/97.8 cm)	34.5 in/38.5 in (87.6 cm/97.8 cm)
DRY WEIGHT (LESS BATTERIES)	530 lb (240.6 kg)	658 lb (298.7 kg)	612 lb (277.8 kg)	724 lb (328.7 kg)
OUTSIDE RADIUS CIRCLE	17.5 ft (5.3 m) dia	17.5 ft (5.3 m) dia	20.7 ft (6.3 m) dia	20.7 ft (6.3 m dia)
TURNING RADIUS	8.4 ft (2.6 m)	8.4 ft (2.6 m)	10 ft (3 m)	10 ft (3 m)
SPEED RANGE	12-15 mph (19.3-24.1 kph)	12-15 mph (19.3-24.1 kph)	5-17 mph (8-27.3 kph)	14-16 mph (22.5-25.7 kph)
VEHICLE WARRANTY	2-year, limited; 4-year batteries	2-year, limited	2-year, limited; 4-year batteries	2-year, limited

\* There are no warranties, express or implied, contained herein. See Limited Warranty found in the owner's manual or write to Club Car, Inc. The company reserves the right to make design changes without obligation to make these changes on units previously sold. These vehicles are designed and manufactured for off-road use only. They do not conform to Federal Motor Vehicle Safety Standards for automobiles or to FMVSS 500 for low-speed vehicles, and are not equipped for operation on public streets, roads or highways.

## 4x2 SPECIFICATIONS

	TURF 6	TURF 252 WITH IQ PLUS™	TURF 252	CARRYALL 232	
	GASOLINE	ELECTRIC	GASOLINE	ELECTRIC	GASOLINE
POWER SOURCE					
ENGINE	Kawasaki 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter	N/A	Kawasaki 4-cycle, OHV, 351 cc, single-cylinder, air-cooled, pressure-lubricated, spin-on oil filter	N/A	Kawasaki 286 cc
DRIVE MOTOR	N/A	48-volt shunt/sepex	N/A	48-volt	N/A
HORSEPOWER	11.5 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards	3.7 hp @ 3,400 rpm (continuous) 21 hp @ 2,000 rpm (peak)	11.5 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards	3.2 hp (continuous)/10 hp (intermittent)	9.5 hp @ 3,600 rpm, exceeds SAE J1940 Performance Standards
GOVERNOR	Automatic ground speed sensing, internally geared-in unitized transaxle	N/A	Automatic ground speed sensing, internally geared-in unitized transaxle	N/A	Automatic ground speed sensing, internally geared-in unitized transaxle
GOVERNED RPM	3,050 +/- 30	N/A	2,900 +/- 30	N/A	3,300 +/- 30
IGNITION	Electronic with electronic RPM limiter	N/A	Electronic with electronic limiter	N/A	Electronic w/electronic RPM limiter
DRIVE UNIT	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse	12.3:1 direct-drive axle, double-reduction helical gear	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse	12.3:1 direct-drive axle, double-reduction helical gear	Unitized transaxle, helical gears, 11.8:1 forward, 17.1:1 reverse
ELECTRICAL SYSTEM	12-volt, 500 cca 105 min reserve	48-volt	12-volt, 500 cca 105 min reserve	48-volt	N/A
BATTERIES	N/A	Eight 6-volt, Standard: T105 = 115 min @ 75 amps; Heavy Duty: T145 = 145 min @ 75 amps	N/A	Six 8-volt	N/A
CHARGER	N/A	Automatic, computer-controlled 48-volt DC, 17 amp, UL and CUL listed	N/A	48-volt variable with on-board computer	N/A
CONTROLLER	N/A	500A solid state	N/A	250 amp solid state	N/A
KEY- OR PEDAL-START	Key	Pedal	Pedal	Pedal	Pedal
STEERING	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion
FRONT SUSPENSION	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
BRAKES	4-wheel mechanical drum	4-wheel, mechanical drum	4-wheel, mechanical drum	Rear-wheel, mechanical drum	Rear-wheel, mechanical drum
PARK BRAKE	Foot-operated, multi-lock	Foot-operated, multi-lock	Foot-operated, multi-lock	Foot-operated	Foot-operated
FRAME/CHASSIS	Aluminum I-beam	Aluminum I-beam	Aluminum I-beam	Aluminum I-beam	Aluminum I-beam
FRONT BODY	ArmorFlex®	ArmorFlex®	ArmorFlex®	ArmorFlex®	ArmorFlex®
REAR BODY	All aluminum	All aluminum	All aluminum	ABS plastic	ABS plastic
TIRES	18 x 6.50-8, 6-ply rated, premium tread	22 x 11-10, 6 ply rated, heavy-duty all-terrain tread	22 x 11-10, 6 ply rated, heavy-duty all-terrain tread	20 x 10-8, 4-ply rated	20 x 10-8, 4-ply rated
INSTRUMENTATION	Electronic fuel gauge/hour meter, low-oil warning light	Electronic fuel gauge/hour meter, low-oil warning light	Electronic fuel gauge/hour meter, low-oil warning light	Battery warning light	Electronic fuel gauge/hour meter, low-oil warning light
CARGO BOX SIZE	70.5 in x 45.1 in x 9.3 in (17.1 ft³) 179.1 cm x 114.6 cm x 23.5 cm	48.4 in x 49.8 in x 10.9 in (123.8 cm x 126.4 cm x 27.6 cm)	48.4 in x 49.8 in x 10.9 in (123.8 cm x 126.4 cm x 27.6 cm)	27.5 in x 43.5 in x 11 in (65.3 cm x 110.5 cm x 27.9 cm)	27.5 in x 43.5 in x 11 in (65.3 cm x 110.5 cm x 27.9 cm)
FLAT BED SIZE	67.6 in x 44.2 in (171.8 cm x 112.2 cm)	46.9 in x 48.3 in (119.1 cm x 122.7 cm)	46.9 in x 48.3 in (119.1 cm x 122.7 cm)	N/A	NA
BED HEIGHT	27 in (68.6 cm)	29.8 in (75.6 cm)	29.8 in (75.6 cm)	28.75"/73cm	28.75"/73cm
BED CAPACITY	1,000 lb (499.4 kg)	500 lb (226.8 kg)	500 lb (226.8 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)
TOTAL VEHICLE CAPACITY	1,500 lb (681 kg)	900 lb (408.2 kg)	900 lb (408.2 kg)	800 lb (363.2 kg)	800 lb (363.2 kg)
OVERALL LENGTH	134 in (340.4 cm)	120.4 in (305.8 cm)	120.4 in (305.8 cm)	100.5 in (255.3 cm)	100.5 in (255.3 cm)
OVERALL WIDTH	49.3 in (125.2 cm)	51.3 in (130.2 cm)	51.3 in (130.2 cm)	49.5 in (125.7 cm)	49.5 in (125.7 cm)
OVERALL HEIGHT	48 in (121.9 cm)	51.1 in (129.8 cm)	51.1 in (129.8 cm)	48 in (121.9 cm)	48 in (121.9 cm)
WHEELBASE	98.5 in (250.2 cm)	78.5 in (199.4 cm)	78.5 in (199.4 cm)	65 in (165.1 cm)	65 in (165.1 cm)
GROUND CLEARANCE	4.5 in (11.4 cm)	6.4 in (16.3 cm)	6.4 in (16.3 cm)	5.5 in (14 cm)	5.5 in (14 cm)
FUEL TANK CAPACITY	5.1 gal (19.2L)	N/A	5.1 gal (19.2L)	N/A	7 gal (26.0 L)
STABILIZER BAR	Yes	No	Yes	N/A	N/A
TREAD	34.5 in/38.6 in (87.6 cm/97.8 cm)	36.5 in/41.3 in (92.7 cm/104.8 cm)	36.5 in/41.3 in (92.7 cm/104.8 cm)	34/38 in. (86.4/96.5 cm)	34/38 in. (86.4/96.5 cm)
DRY WEIGHT (LESS BATTERIES)	868 lb (394.1 kg)	900 lb (408.2 kg)	910 lb (412.8 kg)	874 lb (396.4 kg)	781 lb (354.3 kg)
OUTSIDE RADIUS CIRCLE	24.7 ft (7.5 m) dia	21.7 ft (6.6 m) dia	21.7 ft (6.6 m) dia	-	-
TURNING RADIUS	12 ft (3.7 m)	10.8 ft (3.3 m)	10.8 ft (3.3 m)	8.75 ft (2.7 m)	8.75 ft (2.7 m)
SPEED RANGE	14-16 mph (22.5-25.7 kph)	15-17 mph (24.1-27.4 kph)	15-17 mph (24.1-27.4 kph)	17-19 mph (27.4-30.6 kph)	17-19 mph (27.4-30.6 kph)
VEHICLE WARRANTY	2-year, limited	2-year, limited; 4-year batteries	2-year, limited	2-year, limited	2-year, limited

\* There are no warranties, express or implied, contained herein. See Limited Warranty found in the owner's manual or write to Club Car, Inc. The company reserves the right to make design changes without obligation to make these changes on units previously sold. These vehicles are designed and manufactured for off-road use only. They do not conform to Federal Motor Vehicle Safety Standards for automobiles or to FMVSS 500 for low-speed vehicles, and are not equipped for operation on public streets, roads or highways.

## 4x4 ACCESSORIES\*

# Set Your 4x4 Vehicles On Maximum Performance



Club Car® 4x4 Utility Vehicles are as sophisticated and brawny as they come, and you can get even more performance when you outfit with genuine Club Car accessories. Built tough for the most demanding jobs, Club Car accessories maximize the versatility of your 4x4s. From towing packages and winches to innovative storage and hauling solutions, Club Car accessories let you rig your 4x4 Utility Vehicles to handle the toughest jobs on the course.



Custom Van Box



Rear Cargo Cage



Electric Bed Lift



Underhood Storage  
(Gas Only)



Stake-Side Kit



2-Inch Front  
Receiver Hitch



Cargo Bed Toolbox



2,500 lb. Warn Winch



Pintle Hitch



Nerf Bars



54- or 62-Inch  
Plow Blade



Swisher Trailmower



Swisher  
Dump Cart



40-Gallon Sprayer



Cab Heater  
(Gas Only)



Lighting Package  
(Includes horn, turn  
signals and brake lights)



Plastic Canopy Top

\* For a complete listing of accessories, please contact your local Club Car dealer.

## 4x4 SPECIFICATIONS

	CARRYALL 295		CARRYALL 295 SE		CARRYALL 295 INTELLITACH™
	GASOLINE	DIESEL	GASOLINE	DIESEL	DIESEL
POWER SOURCE					
ENGINE	Kawasaki 4-cycle, OHV, 675 cc, twin-cylinder industrial grade	Kubota D722, 719 cc, 3-cylinder	Kawasaki 4-cycle, OHV, 651 cc, twin-cylinder industrial grade	Kubota D722, 719 cc, 3-cylinder	Kubota D722, 719 cc, 3-cylinder industrial grade
ENGINE-COOLING	Air	Liquid	Air	Liquid	Liquid
ENGINE-LUBRICATION AND OIL FILTER TYPE	Full-pressure, spin-on	Full-pressure, spin-on	Full-pressure, spin-on	Full-pressure, spin-on	Full-pressure, spin-on
MAXIMUM TORQUE	39.8 ft-lb (54.9 Nm)	33 ft-lb (44.7 Nm)	39.8 ft-lb (54.9 Nm)	33 ft-lb (44.7 Nm)	33 ft-lb (44.7 Nm)
HORSEPOWER	23 hp (17.2 kw)	20 hp (14.9 kw)	23 hp (17.2 kw)	20 hp (14.9 kw)	20 hp (14.9 kw)
IGNITION	Transistorized magneto	Compression	Transistorized magneto	Compression	Compression
4WD ENGAGEMENT	Automatic - IntelliTrak	Automatic - IntelliTrak	Automatic - IntelliTrak	Automatic - IntelliTrak	Automatic - IntelliTrak
FRONT DIFFERENTIAL	Automatic - IntelliTrak	Automatic - IntelliTrak	Automatic - IntelliTrak	Automatic - IntelliTrak	Automatic - IntelliTrak
REAR DIFFERENTIAL	Auto locking - IntelliTrak	Auto locking - IntelliTrak	Auto locking - IntelliTrak	Auto locking - IntelliTrak	Auto locking - IntelliTrak
TORQUE CONVERTER	CVT	CVT	CVT	CVT	CVT
ELECTRICAL SYSTEM	12-volt, 500 CCA	12-volt, 500 CCA	12-volt, 500 CCA	12-volt, 500 CCA	12-volt, 500 CCA
STEERING	Rack and pinion	Rack and pinion	Rack and pinion	Rack and pinion	Rack and pinion
TILT STEERING WHEEL	Standard	Standard	Standard	Standard	Standard
FRONT SUSPENSION	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks
REAR SUSPENSION	Swing arm with coil-over shocks	Swing arm with coil-over shocks	Swing arm with coil-over shocks	Swing arm with coil-over shocks	Swing arm with coil-over shocks
BRAKES	4-wheel, hydraulic disc	4-wheel, hydraulic disc	4-wheel, hydraulic disc	4-wheel, hydraulic disc	4-wheel, hydraulic disc
PARK BRAKE	Automotive style	Automotive style	Automotive style	Automotive style	Automotive style
FRAME/CHASSIS	Tubular aluminum	Tubular aluminum	Tubular aluminum	Tubular aluminum	Tubular aluminum
FRONT BODY	GE Gelyol high-impact, scratch-resistant, injection molded color	GE Gelyol high-impact, scratch-resistant, injection molded color	GE Gelyol high-impact, scratch-resistant, injection molded color	GE Gelyol high-impact, scratch-resistant, injection molded color	GE Gelyol high-impact, scratch-resistant, injection molded color
REAR BODY	All aluminum	All aluminum	All aluminum	All aluminum	All aluminum
FRONT TIRES	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply
REAR TIRES	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply
INSTRUMENTATION	Electronic fuel gauge/hour meter, low oil warning light	Electronic fuel gauge/hour meter, low oil warning light, coolant high temp warning light	Electronic fuel gauge/hour meter, low oil warning light	Electronic fuel gauge/hour meter, low oil warning light	Electronic fuel gauge/hour meter, seatbelt warning light, low-oil warning light, coolant high-temp warning light
FLAT BED SIZE	48.8 in x 49.8 in x 10.9 in (124 cm x 126.5 cm x 27.7 cm)	48.8 in x 49.8 in x 10.9 in (124 cm x 126.5 cm x 27.7 cm)	48.8 in x 49.8 in x 10.9 in (124 cm x 126.5 cm x 27.7 cm)	48.8 in x 49.8 in x 10.9 in (124 cm x 126.5 cm x 27.7 cm)	48.8 in x 49.8 in x 10.9 in (123.8 cm x 126.4 cm x 27.6 cm)
BED HEIGHT	33 in (83.8 cm)	33 in (83.8 cm)	33 in (83.8 cm)	33 in (83.8 cm)	33 in (83.8 cm)
BED CAPACITY	800 lb (363.2 kg); 1,050 lb (476.3 kg available)	800 lb (363.2 kg)	800 lb (363.2 kg)	800 lb (363.2 kg)	800 lb (363.2 kg)
TOTAL VEHICLE CAPACITY	1,200 lb (544.3 kg); 1,450 lb (657.7 kg) available	1,200 lb (544.8 kg); 1,450 lb (657.7 kg) available	1,600 lb (725.8 kg)	1,600 lb (725.8 kg)	1,700 lb (771.1 kg)
SEATING	Choice of bucket or bench; Adjustable driver's seat only available with bucket seat option	Choice of bucket or bench; Adjustable driver's seat only available with bucket seat option	Choice of bucket or bench; Adjustable driver's seat only available with bucket seat option	Choice of bucket or bench; Adjustable driver's seat only available with bucket seat option	Bench Seats with adjustable driver's seat
SEATING CAPACITY	2	2	4	4	2
OVERALL LENGTH	124.6 in (316.5 cm)	124.6 in (316.5 cm)	157.6 in (400.3 cm)	157.6 in (400.3 cm)	148.6 in (377.4 cm)
OVERALL WIDTH	60 in (152.4 cm)	60 in (152.4 cm)	60 in (152.4 cm)	60 in (152.4 cm)	60 in (152.4 cm)
OVERALL HEIGHT	78.6 in (199.6 cm)	78.6 in (199.6 cm)	78.6 in (199.6 cm)	78.6 in (199.6 cm)	78.6 in (199.6 cm)
WHEELBASE	88.7 in (225.3 cm)	88.7 in (225.3 cm)	114 in (225.3 cm)	114 in (225.3 cm)	81.5 in (225.3 cm)
GROUND CLEARANCE	7.4 in (18.8 cm)	7.4 in (18.8 cm)	7.4 in (18.8 cm)	7.4 in (18.8 cm)	7.4 in (18.8 cm)
FUEL TANK CAPACITY	6.5 gallons (24.6 L)	6.5 gallons (24.6 L)	6.5 gallons (24.6 L)	6.5 gallons (24.6 L)	6.5 gallons (24.6 L)
TREAD	48.8 in (124 cm)	48.8 in (124 cm)	48.8 in (124 cm)	48.8 in (124 cm)	48.8 in (124 cm)
DRY WEIGHT (LESS BATTERIES)	1,430 lb (648.6 kg)	1,559 lb (707.2 kg)	1,605 lb (728 kg)	1,786 lb (810.1 kg)	1,709 lb (775.1 kg)
MAXIMUM SPEED	25 mph (40.2 kph)	25 mph (40.2 kph)	25 mph (40.2 kph)	25 mph (40.2 kph)	25 mph (40.2 kph)
TURNING RADIUS	13 ft (3.8 m)	13 ft (3.8 m)	17 ft (5.4 m)	17 ft (5.4 m)	13.8 ft (4.2 m)
VEHICLE WARRANTY	2-year, limited	2-year, limited	2-year, limited	2-year, limited	2-year, limited

\* There are no warranties, express or implied, contained herein. See Limited Warranty found in the owner's manual or write to Club Car, Inc. The company reserves the right to make design changes without obligation to make these changes on units previously sold. These vehicles are designed and manufactured for off-road use only. They do not conform to Federal Motor Vehicle Safety Standards for automobiles or to FMVSS 500 for low-speed vehicles, and are not equipped for operation on public streets, roads or highways.



The business of better utility vehicles,  
**that's Club Car's® Turf Line.**

Around the world, the Club Car® name is recognized for the highest levels of performance and quality. We are just as proud of our reputation for helping our customers find solutions that advance their businesses. Nowhere are those solutions more apparent than in our line of utility vehicles for today's golf operations. Through technology, innovation and uncompromising attention to build quality, Club Car is delivering golf's best turf utility vehicles.

We like to think our standing in the industry is a direct result of the high regard we have for the game of golf, and for those who make their livings around it. That regard is reflected in our promise of unmatched performance and unequalled service. No one in the industry invests more in relationships, research, design, engineering, materials and craftsmanship. That's why no one else is Club Car.

Let's talk about putting the finest utility vehicles to work for you.  
Call us at 1.800.CLUBCAR • +1 706.863.3000, or visit us on the web at [clubcar.com](http://clubcar.com).





Ingersoll Rand is a global diversified firm providing products, services and solutions to enhance the quality and comfort of air in homes and buildings, transport and protect food and perishables, secure homes and commercial properties, and increase industrial productivity and efficiency. Driven by a 100-year-old tradition of technological innovation, we enable our customers to create progress and a positive impact in their world.

Please note vehicles contained throughout the brochure may be shown with additional accessories.

1.800.CLUBCAR • +1 706.863.3000

[www.clubcar.com](http://www.clubcar.com)

[www.ingersollrand.com](http://www.ingersollrand.com)

01/10 58648767