



# SVS200

## Single-Port High Output Power



PosiCharge SVS200 can supply 320 Amps with maximum efficiency, making it ideal for hard working distribution centers and manufacturing facilities. Built using sophisticated IGBT technology, the SVS200 is the high output charger of choice for customers looking to combine power with performance.

SVS200 is the high-value charger that supplies safe, intelligent fast-charge power for a wide variety of industries. And like all PosiCharge chargers, the SVS200 works with a broad range of battery voltages and has the same data management and on-board intelligence.

Options include, automatic watering, PosiNet, remote battery and charger management software and ChaMPs, ID Systems IVEC compatibility.

POWER RATING	20 KW
UTILITY REQUIREMENTS	480/600VAC, 3 PHASE
FULL LOAD AMP DRAW	28A/23A MAX
MAX CIRCUIT BREAKER RATING	40A/30A
POWER FACTOR	.98
EFFICIENCY	92%
BATTERY VOLTAGE RANGE	24V – 80V
MAX OUTPUT CURRENT	320A
WEIGHT	470 LBS
DIMENSIONS	41.6" H X 24.5" W X 20.5" D
COMMUNICATION PORT	RS-232

For additional information please contact your authorized TIE dealer  
[www.posichargeTIE.com](http://www.posichargeTIE.com)