



SOLON Top Class


Off-grid sine wave inverter.

13/12 · 15/24

- › Pure sine wave
- › Short circuit and overload security
- › High efficiency factor
- › Galvanic isolation

SOLON Top Class

Off-grid application



Input variables (DC)

		13/12	15/24
Rated voltage DC	$U_{DC IN}$	12 V	24 V
Input voltage range	U_{DC}	10,5 – 16,0 V _{DC}	21,0 – 32,0 V _{DC}
Dynamic low voltage cut (depending on load)	U_{DC}	10,5 – 9,0 V _{DC}	21,0 – 18,0 V _{DC}
Rated current DC	$I_{DC IN}$	125 A	72 A
Max. current	$I_{DC max}$	340 A	140 A

Output variables (AC)


Rated output current AC	$I_{AC OUT}$	5,7 A	6,5 A
Short circuit current (max. 0.5 s)	$I_{AC K}$	16 A	16 A
Continuous power	P_{AC}	1,000 VA	1,200 VA
Rated power (10 min at $T_A = 20^\circ C$)	P_{10}	1,400 VA	1,700 VA
Rated power (30 min at $T_A = 20^\circ C$)	P_{30}	1,300 VA	1,500 VA
Rated output voltage AC (short circuit proof)	$U_{AC OUT}$	230 V _{AC} ± 2 %	230 V _{AC} ± 2 %
Output frequency (pure sine wave)	f_{AC}	50 Hz ± 0,5 %	50 Hz ± 0,5 %
Power factor	$\cos\Phi$	0,3 – 1,0	0,3 – 1,0

Typical data

Dimensions (L x W x H)	385 x 260 x 182 mm	385 x 260 x 182 mm
Weight	15.5 kg	16 kg
Efficiency factor max.	92 %	93 %
Consumption 230 V _{AC} OK	10 W	12 W
DC breaker	No	100 A
Remote control ON/OFF	Yes, external switch	Yes, external switch

Housing protection	IP 20
Status indication	LED
Reset after short circuit	Every 60 s
Reset after overload	Every 60 s
Reset after overtemperature	Automatically after reaching semiconductor temp. 45°C
Reset after battery failure	Automatically after reaching U _{DC IN}

Ambient temperature range	-25°C to +50°C (max. 95 % rH, non-condensing)
Consumption standby/OFF	ca. 0.5 W (testpulse 800 ms)/0 W
Toroidal transformer	Galvanically isolated EN61558 (ICE61558)
Temperature and load controlled fan	ON 55°C/OFF 45°C, P _D > 80 %
Warranty	2 years
Certificate	Declaration of conformity



SOLON Inverters AG
Burgerfeldstrasse 19
8730 Uznach/SG · Switzerland

Phone +41 55 24641-14
Fax +41 55 24641-16
E-Mail inverters@solon.com

SOLON SE
Am Studio 16
12489 Berlin · Germany

Phone +49 30 81879-0
Fax +49 30 81879-9999
E-Mail components@solon.com

SOLON S.p.A.
Via dell'Industria e dell'Artigianato 2
35010 Carmignano di Brenta PD · Italy

Phone +39 049 9458200
Fax +39 049 9458299
E-Mail solon.it@solon.com

Your specialty retailer

For more information on SOLON products visit us on www.solon.com.